

Cicoputty®

High Quality Water Base Multi-Purpose Putty

DESCRIPTION

Cicoputty® is a ready to use water based putty, specially made for fairing and smoothing most walls including gypsum boards, preparing for different finishing water based paints. It is easy to use, directly from the pail to the wall. It doesn't require complicated surface preparation before use. Cicoputty® can be used as a tile adhesive for fixing small ceramic wall tiles, expanded polystyrene tiles, and joint grouting at the same time. It is also suitable for damp and totally submerged conditions. The application thickness range is 0.25 - 2 mm/one go.

USES

- Fine smoothing for walls and partitions including gypsum boards.
- Pre-paints treatment.
- Filling of pin holes and fine hair cracks.
- Uneven plastering surface fine fairing render.
- Tile adhesive.

ADVANTAGES

- Easy to use; ready mixed one component.
- Multi-purpose.
- High adhesion to most construction substrates.
- Compatible with most walls' surfaces.
- Suitable for outside and inside use.
- Water based.
- Economical.

PACKAGING

20 kg pails.

SHELF LIFE & STORAGE

9 months storage life if stored in its original unopened containers under a dry and shaded place in a temperature from 2°C to 45°C.

TECHNICAL PROPERTIES

Form	White Paste
Density @ 25°C	1.68±0.05 Kg/ltr
Working time @ 25°C	25±3 min.
Coverage	12 m²/20 Kg pail @ 1 mm thick

APPLICATION INSTRUCTIONS

Surface Preparation

The application surfaces must be sound, clean, and free from any trace of oil or paint. In hot climates, it is recommended to moisten the substrates slightly prior to applying the putty to avoid fast drying and the loss of wet consistency. For tile adhesive application, moisten the substrates and pre-soak the tiles prior to application. For hair cracks filling, it's recommended to be cleaned by an air blower.

Mixing

Stir Cicoputty® well before use to remix the slight bleeding water if any. This can be done either by a slow drill for 30 seconds or by hand tools.

Application

For painting preparation, apply Cicoputty® on the wall with wide hand putty spreaders to achieve a thin layer every time (not exceeding 0.5 mm). Cicoputty® is elastic and workable enough to give variable layer thickness. For tile fixing, use a notched trowel for 2-3 mm thick application. Press the pre-soaked tiles by gentle twisting action and wipe off surplus adhesive with a damp cloth. Complete each square meter in this way. If the adhesive is spread over a large area at once, skinning might occur and cause adhesive failure. Joint grouting using Cicotile® Joint Grout or Cicoputty® can start 24 hours after fixing.

CLEANING

Tools freshly contaminated with Cicoputty® may be cleaned using clean water. Hard material can be removed by hand tools or light mechanical means.

PRECAUTIONS

Health And Safety

Cicoputty® is non-hazardous. However, it should not be swallowed or allowed to come into contact with skin or eyes. Suitable protective goggles should be worn. Splashes on the skin should be removed with water. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, seek medical attention immediately. Do not induce vomiting.

TECHNICAL SUPPORT

CIC provides on-site assistance, as well as consulting services on projects when requested. Technical data sheets on other CIC products and guidance on their use are available on request.



Warranty

CIC products are guaranteed against defective materials and manufacture and sold subject to CIC's standard terms and conditions of sale. Whilst CIC endeavors to ensure that any advice, information or recommendation given is correct, the company cannot accept any liability either directly or indirectly arising from the use of its products. User of the product must test the product's suitability for the intended application and purpose, since the company has no control over the application of its products. Information contained in this document is given on the best current knowledge. Our Products are in continuous development and CIC reserves the right to change the product without prior notice.

Jeddah Head Office

Jeddah tower building -
SHARFIYA - PO BOX
7232 JEDDAH 21462
+9666532152
info@cictg.com

Central Region

Khurais road-Al Rabwa
Near Gulf Bridge Riyadh
+966 11-4937635
+96611-4939213

Eastern Region

Alkhuzayem 2/7446 King
Abdulaziz Rd Madinat Al
Umal-AlKhobar 34441
4759

Jeddah Factory

Modon Phase 3, Jizan
Road, Jeddah, Saudi
Arabia

Jubail Factory

2882 Road 118- 1St
Industrial Area Unit
No 69